



Connect UP&D

Lavov linear luminaire from the family Viewline Connect UP&D with a power of 84W and a beam angle of 65 degrees. CCT 4000K and UGR16.With a real lumen output of 4000+6000lm and a luminous efficiency of 119.04lm/w. Driver DALI . Finished in black color.

| Item code | 86.L006.3413.02 | | |
|--------------|----------------------------------|--|--|
| Product type | Indoor Linear Systems Viewline | | |
| Category | | | |
| Family | | | |
| Subfamily | Connect UP&D | | |
| Pictograms | 220 v CRI C € Driver INCL. | | |
| | On IP 20 | | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 84 | |
| Real luminous flux (Lm) | 4200+6300 | |
| Luminous efficiency (Lm/W) | 125 | |
| Beam angle (º) | 65 | |
| Colour | black | |
| U. G. R | <16 | |
| Chip Brand | philip | |
| Control gear included | yes | |
| Control gear | DALI | |
| Light source | LED | |
| Type of LED | SMD | |
| Average life time (h) | 50000h L80B10 | |
| Colour temperature (K) | 4000 | |
| Colour consistency (SDCM) | <3SDCM | |
| CRI | >80 | |
| IK | IK02 | |

| Scheme | - | |
|--------|--------|------|
| - | 3000mm | 65mm |
| | | |