



NEON CSP

Lavov LED strip from the family NEON FRONT with a power of 10W/m and an optics 106 degrees beam angle. CCT 3000K. With a total lumen output of 555lm/m and an efficacy of 55lm/W

| | |
|------------------|------------------------|
| Item code | 86.LN04.1300.90 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | LED Strips |
|-----------------|-------------------|

| | |
|---------------|-------------------|
| Family | NEON FRONT |
|---------------|-------------------|

| | |
|------------------|-----------------|
| Subfamily | NEON CSP |
|------------------|-----------------|

| | |
|-------------------|--|
| Pictograms | <div style="display: flex; gap: 5px;"> <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 5px;">CRI 90</div> <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 5px;">Driver EXCL.</div> <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 5px;">50000h L70B10</div> </div> |
|-------------------|--|

Product

| | |
|-----------------------|-----------|
| Real power (W) | 10 |
|-----------------------|-----------|

| | |
|--------------------------------|------------|
| Real luminous flux (Lm) | 555 |
|--------------------------------|------------|

| | |
|-----------------------------------|-----------|
| Luminous efficiency (Lm/W) | 55 |
|-----------------------------------|-----------|

| | |
|-----------------------|------------|
| Beam angle (°) | 106 |
|-----------------------|------------|

| | |
|----------------------|---------------|
| Life time (h) | 30000h |
|----------------------|---------------|

| | |
|-----------|-----------|
| IP | 68 |
|-----------|-----------|

| | |
|---------------------------|------------|
| Electrical feeding | 24V |
|---------------------------|------------|

| | |
|-------------------|---------------|
| Chip Brand | Refond |
|-------------------|---------------|

| | |
|------------------------------|------------|
| Control gear included | not |
|------------------------------|------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|------------|
| Type of LED | CSP |
|--------------------|------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 90 |
|------------|-----------|

Dimensions

Product dimensions (mm) PCB 8mm width, body 10X10x 5000 mm length, cut every 50 mm, 320 CSP led/m.

Scheme

