



SLINER

Lavov linear system from the family SLINER with a power of 30W and an optics 77 degrees beam angle. CCT 3000. CRI 80. Microprismatic diffuser. UGR19. With a total lumen output of 3600lm and an efficacy of 120lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

| | | | | | |
|--------------|---|--|--|--|--|
| Item code | 86.LR01.2391.02 | | | | |
| Product type | Indoor | | | | |
| Category | Linear Systems | | | | |
| Family | SLINER | | | | |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div></div> <div><div>On Off</div><div> 1-10V</div><div>IP 20</div><div>50000h L80B10</div></div> | | | | |

| | |
|-------------------------|----------------------|
| Dimensions | |
| Product dimensions (mm) | Hole size 1206xW50mm |

| | |
|--------|--|
| Scheme | |
| | |

| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 30 |
| Real luminous flux (Lm) | 3600 |
| Luminous efficiency (Lm/W) | 120 |
| Beam angle (º) | 77 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| Colour | Black |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |