



### SLINER

Lavov linear system from the family SLINER with a power of 45W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 133lm/W . Made in Extruded Aluminium and finished in Black color. 0-10V Dim driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.LR01.3302.02</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                       |
|-----------------|-----------------------|
| <b>Category</b> | <b>Linear Systems</b> |
|-----------------|-----------------------|

|               |               |
|---------------|---------------|
| <b>Family</b> | <b>SLINER</b> |
|---------------|---------------|

**Pictograms**



### Dimensions

**Product dimensions (mm)**    **Hole size 1803xW50mm**

### Scheme



### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>45</b> |
|-----------------------|-----------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>6000</b> |
|--------------------------------|-------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>133</b> |
|-----------------------------------|------------|

|                       |            |
|-----------------------|------------|
| <b>Beam angle (°)</b> | <b>110</b> |
|-----------------------|------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                |           |
|----------------|-----------|
| <b>U. G. R</b> | <b>22</b> |
|----------------|-----------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>Yes</b> |
|------------------------------|------------|

|                     |                  |
|---------------------|------------------|
| <b>Control gear</b> | <b>0-10V Dim</b> |
|---------------------|------------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>3000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>80</b> |
|------------|-----------|