



## **MLINER**

Lavov linear system from the family MLINER with a power of  $15\mathrm{W}$ and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 2000lm and an efficacy of 133 Im/W . Made in Extruded Aluminium and finished in White color. 0-10V Dim driver.

| Item code    | 86.LR02.1402.01            |  |  |
|--------------|----------------------------|--|--|
| Product type | Indoor<br>Linear Systems   |  |  |
| Category     |                            |  |  |
| Family       | MLINER                     |  |  |
| Pictograms   | 220 v CRI C C Driver INCL. |  |  |
|              | On IP 50000h L80B10        |  |  |

| Product                    |               |  |
|----------------------------|---------------|--|
| Real power (W)             | 15            |  |
| Real luminous flux (Lm)    | 2000          |  |
| Luminous efficiency (Lm/W) | 133           |  |
| Beam angle (º)             | 110           |  |
| Life time (h)              | 50000h L80B10 |  |
| IP                         | 20            |  |
| Colour                     | White         |  |
| U. G. R                    | 22            |  |
| Control gear included      | Yes           |  |
| Control gear               | 0-10V Dim     |  |
| Colour temperature (K)     | 4000          |  |
| Colour consistency (SDCM)  | SDCM<3        |  |
| CRI                        | 80            |  |

## **Dimensions** Product dimensions (mm) Hole size 606xW75mm

| Scheme |    |     |
|--------|----|-----|
| 90     | 1  | 621 |
|        | 88 |     |
| 75     |    | 606 |