



**MLINER**

Lavov linear system from the family MLINER with a power of 15W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 2000lm and an efficacy of 133lm/W . Made in Extruded Aluminium and finished in White color. DALI driver.

<b>Item code</b>	<b>86.LR02.1403.01</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>MLINER</b>

**Pictograms**



**Dimensions**

**Product dimensions (mm)**    **Hole size 606xW75mm**

**Scheme**



<b>Product</b>	
<b>Real power (W)</b>	<b>15</b>
<b>Real luminous flux (Lm)</b>	<b>2000</b>
<b>Luminous efficiency (Lm/W)</b>	<b>133</b>
<b>Beam angle (°)</b>	<b>110</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>20</b>
<b>Colour</b>	<b>White</b>
<b>U. G. R</b>	<b>22</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>