



**MLINER**

Lavov linear system from the family MLINER with a power of 15W and an optics 77 degrees beam angle. CCT 4000. CRI 80.

Microprismatic diffuser. UGR

|                     |                        |
|---------------------|------------------------|
| <b>Item code</b>    | <b>86.LR02.1491.02</b> |
| <b>Product type</b> | <b>Indoor</b>          |
| <b>Category</b>     | <b>Linear Systems</b>  |
| <b>Family</b>       | <b>MLINER</b>          |

**Pictograms**

|           |              |           |                  |                 |
|-----------|--------------|-----------|------------------|-----------------|
|           | 220<br>240 V | CRI<br>80 | CE               | Driver<br>INCL. |
| On<br>Off | <br>1-10V    | IP<br>20  | 50000h<br>L80B10 |                 |

**Dimensions**

**Product dimensions (mm)    Hole size 606xW75mm**

**Scheme**



**Product**

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Real power (W)</b>             | <b>15</b>            |
| <b>Real luminous flux (Lm)</b>    | <b>1800</b>          |
| <b>Luminous efficiency (Lm/W)</b> | <b>120</b>           |
| <b>Beam angle (°)</b>             | <b>77</b>            |
| <b>Life time (h)</b>              | <b>50000h L80B10</b> |
| <b>IP</b>                         | <b>20</b>            |
| <b>Colour</b>                     | <b>Black</b>         |
| <b>U. G. R</b>                    | <b>&lt;19</b>        |
| <b>Control gear included</b>      | <b>Yes</b>           |
| <b>Control gear</b>               | <b>ON-OFF</b>        |
| <b>Colour temperature (K)</b>     | <b>4000</b>          |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>     |
| <b>CRI</b>                        | <b>80</b>            |