



MLINER

Lavov linear system from the family MLINER with a power of 30W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 4000lm and an efficacy of 133lm/W . Made in Extruded Aluminium and finished in Black color. DALI driver.

| | |
|------------------|------------------------|
| Item code | 86.LR02.2303.02 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-----------------------|
| Category | Linear Systems |
|-----------------|-----------------------|

| | |
|---------------|---------------|
| Family | MLINER |
|---------------|---------------|

| | |
|-------------------|---|
| Pictograms |      |
| |     |

220
240 VCRI
80Driver
INCL.On
Off

1-10V

IP
2050000h
L80B10

Dimensions

| | |
|--------------------------------|-----------------------------|
| Product dimensions (mm) | Hole size 1206xW75mm |
|--------------------------------|-----------------------------|

Scheme



Product

| | |
|-----------------------|-----------|
| Real power (W) | 30 |
|-----------------------|-----------|

| | |
|--------------------------------|-------------|
| Real luminous flux (Lm) | 4000 |
|--------------------------------|-------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 133 |
|-----------------------------------|------------|

| | |
|-----------------------|------------|
| Beam angle (°) | 110 |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L80B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|----------------|-----------|
| U. G. R | 22 |
|----------------|-----------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|-------------|
| Control gear | DALI |
|---------------------|-------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|