



MLINER

Lavov linear system from the family MLINER with a power of 45W and an optics 110 degrees beam angle. CCT 3000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 133lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

|              |  |
|--------------|--|
| Item code    | 86.LR02.3301.02  |
| Product type | Indoor   |
| Category     | Linear Systems   |
| Family       | MLINER   |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div>CRI<br/>80</div><div>CE</div><div>Driver<br/>INCL.</div></div> <div><div>On<br/>Off</div><div>1-10V</div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |

|                         |                      |
|-------------------------|----------------------|
| Dimensions              |                      |
| Product dimensions (mm) | Hole size 1803xW75mm |

|        |  |
|--------|--|
| Scheme |  |
|        |  |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 45            |
| Real luminous flux (Lm)    | 6000          |
| Luminous efficiency (Lm/W) | 133           |
| Beam angle (º)             | 110           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20            |
| Colour                     | Black         |
| U. G. R                    | 22            |
| Control gear included      | Yes           |
| Control gear               | ON-OFF        |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |