



### MLINER

Lavov linear system from the family MLINER with a power of 60W and an optics 110 degrees beam angle. CCT 4000. CRI 80. PC Diffuser. UGR22. With a total lumen output of 6000lm and an efficacy of 133lm/W . Made in Extruded Aluminium and finished in Black color. ON-OFF driver.

<b>Item code</b>	<b>86.LR02.4401.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Linear Systems</b>
-----------------	-----------------------

<b>Family</b>	<b>MLINER</b>
---------------	---------------

**Pictograms**



### Dimensions

**Product dimensions (mm)**    **Hole size 2402xW75mm**

### Scheme



### Product

<b>Real power (W)</b>	<b>60</b>
-----------------------	-----------

<b>Real luminous flux (Lm)</b>	<b>6000</b>
--------------------------------	-------------

<b>Luminous efficiency (Lm/W)</b>	<b>133</b>
-----------------------------------	------------

<b>Beam angle (°)</b>	<b>110</b>
-----------------------	------------

<b>Life time (h)</b>	<b>50000h L80B10</b>
----------------------	----------------------

<b>IP</b>	<b>20</b>
-----------	-----------

<b>Colour</b>	<b>Black</b>
---------------	--------------

<b>U. G. R</b>	<b>22</b>
----------------	-----------

<b>Control gear included</b>	<b>Yes</b>
------------------------------	------------

<b>Control gear</b>	<b>ON-OFF</b>
---------------------	---------------

<b>Colour temperature (K)</b>	<b>4000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>80</b>
------------	-----------