



HI. EFF. STRIP

Lavov LED strip from the family with a power of 9,6W/m and an optics 120 degrees beam angle. CCT 3000K. With a total lumen output of 1056lm/m and an efficacy of 110lm/W

| Item code | 86.LS03.2300.9F Indoor | | | | |
|--------------|---|--|--|--|--|
| Product type | | | | | |
| Category | LED Strips | | | | |
| Family | HI. EFF. STRIP | | | | |
| Pictograms | CRI Driver IP 50000h 80 EXCL 20 L70B10 | | | | |

| Dimensions | |
|-------------------------|--|
| Product dimensions (mm) | PCB 8mm x 5m trimmable 50 mm, 160 LED/m |

| | | 7.0 | lmm | | | |
|------|--|-----|----------|------|----------|---|
| | | 7.6 | <u>-</u> | | | |
| | | | | | т | L |
| +24V | | | | +24V | ↑ | |
| | | | | | 817 | |

Trimmable:62.5mm

| Product | | | |
|----------------------------|------------------|--|--|
| Real power (W) | 9.6 | | |
| Real luminous flux (Lm) | 1056 | | |
| Luminous efficiency (Lm/W) | 110 | | |
| Beam angle (º) | 120 | | |
| Life time (h) | 50000h L70B10 | | |
| IP | 20 | | |
| Chip Brand | Refond | | |
| Control gear included | not | | |
| Type of LED | 2835 SMD | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 90 Full spectrum | | |

Scheme

1.1mm