



## HI. EFF. STRIP

Lavov LED strip from the family with a power of 14,4W/m and an optics 120 degrees beam angle. CCT 6500K. With a total lumen output of 1728lm/m and an efficacy of 120lm/W

| 86.LS03.4600.90 |
|-----------------|
| Indoor          |
| LED Strips      |
| HI. EFF. STRIP  |
|                 |

**Pictograms** 

| Dimensions              |                         |  |  |  |  |
|-------------------------|-------------------------|--|--|--|--|
| Product dimensions (mm) | PCB 10mm x 5m trimmable |  |  |  |  |
|                         | 62,5 mm, 128 LED/m      |  |  |  |  |

|      |   |          | 7.8 | Imm |      |     |  |
|------|---|----------|-----|-----|------|-----|--|
| +24V | 0 | <u> </u> |     |     | +24V | 0mm |  |

Scheme

| Product                    |               |
|----------------------------|---------------|
| Real power (W)             | 14.4          |
| Real luminous flux (Lm)    | 1728          |
| Luminous efficiency (Lm/W) | 120           |
| Beam angle (º)             | 120           |
| Life time (h)              | 50000h L70B10 |
| IP                         | 20            |
| Chip Brand                 | Refond        |
| Control gear included      | not           |
| Type of LED                | 2835 SMD      |
| Colour temperature (K)     | 6500          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 90            |