



### HI. EFF. STRIP IP66

Lavov LED strip from the family HI. EFF. STRIP IP66 with a power of 14,4W/m and an optics 120 degrees beam angle. CCT 2700K. IP66. With a total lumen output of 1296lm/m and an efficacy of 90lm/W

<b>Item code</b>	<b>86.LS13.1200.90</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>LED Strips</b>
<b>Family</b>	<b>HI. EFF. STRIP IP66</b>
<b>Pictograms</b>	<div style="display: flex; gap: 5px;"> <div style="border: 1px solid gray; padding: 2px;">CRI 90</div> <div style="border: 1px solid gray; padding: 2px;">Driver EXCL.</div> <div style="border: 1px solid gray; padding: 2px;">IP 66</div> <div style="border: 1px solid gray; padding: 2px;">50000h L70B10</div> </div>

### Product

<b>Real power (W)</b>	<b>14.4</b>
<b>Real luminous flux (Lm)</b>	<b>1296</b>
<b>Luminous efficiency (Lm/W)</b>	<b>90</b>
<b>Beam angle (°)</b>	<b>120</b>
<b>Life time (h)</b>	<b>50000h L70B10</b>
<b>IP</b>	<b>66</b>
<b>Chip Brand</b>	<b>Refond</b>
<b>Control gear included</b>	<b>not</b>
<b>Type of LED</b>	<b>2835 SMD</b>
<b>Colour temperature (K)</b>	<b>2700</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>90</b>

### Dimensions

**Product dimensions (mm)** PCB 10mm x 5m trimmable  
50 mm, 140 LED/m

### Scheme

