




## HI. EFF. STRIP IP66

Lavov LED strip from the family HI. EFF. STRIP IP66 with a power of 14,4W/m and an optics 120 degrees beam angle. CCT 2700K. IP66.With a total lumen output of 1296lm/m and an efficacy of 90lm/W

| Item code    | 86.LS13.1200.90 Indoor LED Strips         |  |
|--------------|---|--|
| Product type |   |  |
| Category     |   |  |
| Family       | HI. EFF. STRIP IP66                       |  |
| Pictograms   | CRI Driver IP 50000h<br>90 EXCL 66 L70B10 |  |

| Dimensions         |                                |
|--------------------|--------------------------------|
| Product dimensions | PCB 10mm x 5m trimmable 50 mm, |
| (mm)               | 140 LED/m                      |

## Scheme



| Product                    |               |
|----------------------------|---------------|
| Real power (W)             | 14.4          |
| Real luminous flux (Lm)    | 1296          |
| Luminous efficiency (Lm/W) | 90            |
| Beam angle (º)             | 120           |
| Life time (h)              | 50000h L70B10 |
| IP                         | 66            |
| Chip Brand                 | Refond        |
| Control gear included      | not           |
| Type of LED                | 2835 SMD      |
| Colour temperature (K)     | 2700          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 90            |