


**CSP IP54 480 LED/m**

Lavov LED strip from the family CSP IP54 480 LED/m with a power of 14,4W/m and an optics 124 degrees beam angle. CCT 4000K. With a total lumen output of 1353,6lm/m and an efficacy of 94lm/W

|                     |  |
|---------------------|--|
| <b>Item code</b>    | <b>86.LS26.3400.90</b>   |
| <b>Product type</b> | <b>Indoor</b>  |
| <b>Category</b>     | <b>LED Strips</b>  |
| <b>Family</b>       | <b>CSP IP54</b>  |
| <b>Subfamily</b>    | <b>CSP IP54 480 LED/m</b>  |
| <b>Pictograms</b>   | <div style="display: flex; gap: 5px;"> <div style="border: 1px solid gray; padding: 2px;">CRI<br/>90</div> <div style="border: 1px solid gray; padding: 2px;">Driver<br/>EXCL.</div> <div style="border: 1px solid gray; padding: 2px;">50000h<br/>L70B10</div> </div> |

**Dimensions**

**Product dimensions (mm)** PCB 8mm width by 5000 mm length, cut every 50 mm, 480 CSP led/m

**Scheme**

**Product**

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Real power (W)</b>             | <b>14.4</b>          |
| <b>Real luminous flux (Lm)</b>    | <b>1353.6</b>        |
| <b>Luminous efficiency (Lm/W)</b> | <b>94</b>            |
| <b>Beam angle (°)</b>             | <b>124</b>           |
| <b>Life time (h)</b>              | <b>50000h L70B10</b> |
| <b>IP</b>                         | <b>54</b>            |
| <b>Chip Brand</b>                 | <b>Refond</b>        |
| <b>Control gear included</b>      | <b>not</b>           |
| <b>Colour temperature (K)</b>     | <b>4000</b>          |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>     |
| <b>CRI</b>                        | <b>90</b>            |