



## CSP IP68 480 LED/m

Lavov LED strip from the family CSP IP68 480 LED/m with a power of 14,4W/m and an optics 120 degrees beam angle. CCT 6500K. With a total lumen output of 1324,8lm/m and an efficacy of 92lm/W

| ltem code    | 86.LS27.2600.90                      |  |  |  |  |  |  |
|--------------|--------------------------------------|--|--|--|--|--|--|
| Product type | Indoor                               |  |  |  |  |  |  |
| Category     | LED Strips                           |  |  |  |  |  |  |
| Family       | CSP IP68                             |  |  |  |  |  |  |
| Subfamily    | CSP IP68 480 LED/m                   |  |  |  |  |  |  |
| Pictograms   | CRI Driver 50000h<br>90 EXCL. L70B10 |  |  |  |  |  |  |

## Dimensions

Product

PCB 8mm width by 5000 mm length, dimensions (mm) cut every 50 mm, 480 CSP led/m

| che               | me   |     |  |  |   |  |  |     |      |  |   |  |
|-------------------|------|-----|--|--|---|--|--|-----|------|--|---|--|
| 8                 | +24V | 8+8 |  |  | 8 |  |  | 8+8 | +24V |  | 5 |  |
| ◄ Trimmable: 50mm |      |     |  |  |   |  |  |     | 5mn  |  |   |  |

| Product                    |               |  |  |  |  |
|----------------------------|---------------|--|--|--|--|
| Real power (W)             | 14.4          |  |  |  |  |
| Real luminous flux (Lm)    | 1324.8        |  |  |  |  |
| Luminous efficiency (Lm/W) | 92            |  |  |  |  |
| Beam angle (º)             | 120           |  |  |  |  |
| Life time (h)              | 50000h L70B10 |  |  |  |  |
| IP                         | 68            |  |  |  |  |
| Chip Brand                 | Refond        |  |  |  |  |
| Control gear included      | not           |  |  |  |  |
| Colour temperature (K)     | 6500          |  |  |  |  |
| Colour consistency (SDCM)  | SDCM<3        |  |  |  |  |
| CRI                        | 90            |  |  |  |  |

