


**Individual UP&D Smart**

Lavov linear luminaire from the family Viewline Individual UP&D with a power of 42W and a beam angle of 65 degrees. CCT 4000K and UGR16. With a real lumen output of 2000+3000lm and a luminous efficiency of 119,04lm/w. Dimable driver Casambi ready. . Finished in white color.

<b>Item code</b>	<b>86.LST5.2419.01</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Linear Systems</b>
<b>Family</b>	<b>Viewline</b>
<b>Subfamily</b>	<b>Individual UP&amp;D Smart</b>
<b>Pictograms</b>	

**Scheme**



<b>Product</b>	
<b>Real power (W)</b>	<b>42</b>
<b>Real luminous flux (Lm)</b>	<b>2100+3150</b>
<b>Luminous efficiency (Lm/W)</b>	<b>125</b>
<b>Beam angle (°)</b>	<b>65</b>
<b>Colour</b>	<b>white</b>
<b>U. G. R</b>	<b>&lt;16</b>
<b>Chip Brand</b>	<b>philip</b>
<b>Control gear included</b>	<b>yes</b>
<b>Control gear</b>	<b>Dimable Casambi ready</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>50000h L80B10</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>&lt;3SDCM</b>
<b>CRI</b>	<b>&gt;80</b>
<b>IK</b>	<b>IK02</b>