




Scheme



Connect UP&D Smart

Lavov linear luminaire from the family Viewline Connect UP&D with a power of 42W and a beam angle of 65 degrees. CCT 4000K and UGR16. With a real lumen output of 2000+3000lm and a luminous efficiency of 119,04lm/w. Dimable driver Casambi ready. . Finished in black color.

| | |
|--------------|---|
| Item code | 86.LST6.2419.02 |
| Product type | Indoor |
| Category | Linear Systems |
| Family | Viewline |
| Subfamily | Connect UP&D Smart |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div></div> <div><div>On Off</div><div></div><div>IP 20</div></div> |

| | |
|----------------------------|-----------------------|
| Product | |
| Real power (W) | 42 |
| Real luminous flux (Lm) | 2100+3150 |
| Luminous efficiency (Lm/W) | 125 |
| Beam angle (°) | 65 |
| Colour | black |
| U. G. R | <16 |
| Chip Brand | philip |
| Control gear included | yes |
| Control gear | Dimable Casambi ready |
| Light source | LED |
| Type of LED | SMD |
| Average life time (h) | 50000h L80B10 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | <3SDCM |
| CRI | >80 |
| IK | IK02 |