





Scheme












Photometry



CONE COVER

Outdoor Bollards from the family CONE COVER with a power of 12W and an Assymetric lighting distribution. Dimmensions pole diam. 118mm and 500mm height. Real lumen output of 800lm and an efficiency of 66.67lm/W . With a CCT of 3000K. IP65 and IK08 degree of protection. Made in Die Cast Aluminium Body, Extruded Aluminum Pole and finished in Black color.ON-OFF driver.

Item code	86.OB07.1311.02
Product type	Outdoor
Category	Bollards
Family	CONE COVER
Pictograms	<div><div>50 60 Hz</div><div>220 240 V</div><div>CRI 80</div><div>SDCM 3</div><div></div><div>Driver INCL.</div><div>50000h L70B10</div><div>IP 65</div><div>IK 08</div></div>

Product	
Real power (W)	12
Real luminous flux (Lm)	800
Luminous efficiency (Lm/W)	66.67
Beam angle (°)	Assymetric
Life time (h)	50000h L70B10
IP	65
Electrical class insulation	Class I
Colour	Black
Chip Brand	SUNPU
Control gear included	yes
Control gear	ON-OFF
Light source	LED
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	75
IK	IK08