



PATH

Lavov bollard from the family Path with a power of 15W and an optic of Assymetric type V. with a real lumen output of 1500lm and an efficiency of 100lm/W with a CCT of 3000K, made in Extruded Aluminium, die cast body, and finished in Black color. ON-OFF+ pressence detector driver. Degree of protection IP66 and IKIK10.

Item code	86.OB10.1312.02									
Product type	Outdoor									
Category	Bollards									
Family	PATH									
Pictograms	<div><div></div><div>50 60 Hz</div><div>220 240 V</div><div></div><div>850°</div><div>IK 10</div></div> <div><div>CRI 80</div><div>SDCM 3</div><div>CE</div><div>Driver INCL.</div><div></div></div> <div><div>IP 66</div><div>50000h L70B10</div></div>									

Product	
Real power (W)	15
Real luminous flux (Lm)	1500
Luminous efficiency (Lm/W)	100
Beam angle (°)	Assymetric type V
Life time (h)	50000h L70B10
IP	66
Electrical class insulation	Class I
Colour	Black
Control gear included	yes
Control gear	ON-OFF+ pressence detector
Light source	LED
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80
IK	IK10

Dimensions

Product dimensions (mm) $\Phi 135 \times 500 \text{mm}$

Scheme

