



PATH

Lavov bollard from the familly Path with a power of 25W and an optic of Assymetric type V. with a real lumen output of 2500lm and an efficiency of 100lm/W with a CCT of 3000K, made in Extruded Aluminium, die cast body, and finished in Black color. ON-OFF+ pressence detector driver. Degree of protection IP66 and IKIK10.

Item code	86.0B10.2312.02 Outdoor Bollards PATH	
Product type Category		
Pictograms		
	CRI SDCM C C Driver INCL.	
	IP 50000h 66 L70B10	


	Product type	Outdoor	
	Category	Bollards	
	Family	PATH	
	Pictograms	50 Hz 220 V	
	- -	CRI SDCM C E Driver INCL.	
Ф135×1000mm		IP 50000h 66 L70B10	

ΙK

Scheme

Dimensions

Product dimensions (mm)



Product	
Real power (W)	25
Real luminous flux (Lm)	2500
Luminous efficiency (Lm/W)	100
Beam angle (º)	Assymetric type V
Life time (h)	50000h L70B10
IP	66
Electrical class insulation	Class I
Colour	Black
Control gear included	yes
Control gear	ON-OFF+ pressence detector
Light source	LED
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80

IK10

Photometry

