











### MINI SPOT B

Lavov bollard from the family MINI SPOT B, base version, with a power of 6W and a 33 degrees beam angle. Finished in White colour. Dimensions  $\varnothing 45*130*H820$ mm.. With a total lumen output of 418lm and a luminous efficiency of 70lm/W. CCT 3000K. Driver ON-OFF. Made in Die Cast Aluminium Body, extruded aluminium pole. .IP54.

#### Dimensions

Product dimensions (mm)  $\varnothing 45*130*H820$ mm

#### Scheme

|              |   |
|--------------|---|
| Item code    | 86.OB20.2321.01   |
| Product type | Outdoor   |
| Category     | Bollards  |
| Family       | MINI SPOT   |
| Subfamily    | MINI SPOT B   |
| Pictograms   |     <br>   |

|                            |                    |
|----------------------------|--------------------|
| Product                    |                    |
| Real power (W)             | 6                  |
| Real luminous flux (Lm)    | 418                |
| Luminous efficiency (Lm/W) | 69.666666666666998 |
| Beam angle (°)             | 33                 |
| Life time (h)              | 50000h L80B10      |
| IP                         | IP54               |
| Colour                     | White              |
| Control gear included      | Yes                |
| Control gear               | ON-OFF             |
| Light source               | LED                |
| Type of LED                | COB                |
| Colour temperature (K)     | 3000               |
| Colour consistency (SDCM)  | SDCM3              |
| CRI                        | 90                 |

