



### PILAR

Surface Ceiling Downlight fixture from the family PILAR with a power of 19.5 W and a 36 degrees beam angle. With a real lumen output of 2098lm and a luminous efficiency of 107.6lm/W. Made in Die Cast Aluminium Body, Front Cover Tempered Glass with an IP65 and an IK06 degree of protection. Finished in Black color. ON-OFF driver included

**Item code** 86.OC01.1331.02

**Product type** Outdoor

**Category** Surface Ceiling Downlight

**Family** PILAR

**Pictograms**

	50 60 Hz	220 240 V		CRI 80
SDCM 3	CE	Driver INCL.		50000h L80B10
IP 65	IK 06			

### Product

**Real power (W)** 19.5

**Real luminous flux (Lm)** 2098

**Luminous efficiency (Lm/W)** 107.6

**Beam angle (°)** 36

**Life time (h)** 50000h L80B10

**IP** 65

**Electrical class insulation** Class I

**Colour** Black

**Control gear included** Yes

**Control gear** ON-OFF

**Light source** LED

**Type of LED** 1\*18W Nichia COB


**Colour temperature (K)** 3000

**Colour consistency (SDCM)** SDCM<3

**CRI** >80

**IK** IK06

### Scheme



### Photometry

