



Bracket

Lavov Floodlight from the family COURT with a power of 150W $\,$ and a 50x90 degrees beam angle. With a total lumen output of 21000lm and a luminous efficiency of 140lm/W. Made in Body Aluminium alloy materials - AL6063 and Steel Q235 with powder coating. PC lenses. and finished in black colour. IP65 and IK10 degree of protection ON-OFF driver.

| Item code | 86.OF01.3451.02 | | |
|--------------|----------------------------|--|--|
| Product type | Outdoor | | |
| Category | Floodlights | | |
| Family | COURT | | |
| Subfamily | Bracket | | |
| Pictograms | Sov CE Driver CRI 1NCL. 70 | | |
| | SDCM IP 65 | | |

| Family Subfamily Pictograms | Floodlights COURT Bracket | | | |
|-----------------------------|-----------------------------|--|--|------------|
| | | | | SDCM IP 65 |
| | | | | Product |

447

| Product | |
|----------------------------|-----------------------|
| Real power (W) | 150 |
| Real luminous flux (Lm) | 21000 |
| Luminous efficiency (Lm/W) | 140 |
| Beam angle (º) | 50x90 |
| IP | IP65 |
| Colour | black |
| Control gear included | yes |
| Control gear | ON-OFF |
| Light source | LED |
| Type of LED | NF2W757GR-V3 |
| Average life time (h) | Up to 100,000hrs LM70 |
| Colour temperature (K) | 4500K |
| Colour consistency (SDCM) | <5 |
| CRI | 75 |
| IK | IK10 |

Scheme

300