



AREA

Lavov floodlight from the family AREA with a power of 300W and a 90x60 degrees beam angle . With a real lumen output of 36000lm and a luminous efficiency of 120lm/W. CRI >75, CCT 4500K. degree of protection. Made in Body Aluminium alloy materials - AL6063 and Steel Q235 with powder coating. PC lenses. and finished in grey color. Driver ON-OFF.

| | |
|------------------|------------------------|
| Item code | 86.OF02.4431.03 |
|------------------|------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|--------------------|
| Category | Floodlights |
|-----------------|--------------------|

| | |
|---------------|-------------|
| Family | AREA |
|---------------|-------------|

Pictograms

Product

| | |
|-----------------------|------------|
| Real power (W) | 300 |
|-----------------------|------------|

| | |
|--------------------------------|--------------|
| Real luminous flux (Lm) | 36000 |
|--------------------------------|--------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 120 |
|-----------------------------------|------------|

| | |
|-----------------------|--------------|
| Beam angle (°) | 90x60 |
|-----------------------|--------------|

| | |
|-----------|-------------|
| IP | IP65 |
|-----------|-------------|

| | |
|---------------|-------------|
| Colour | grey |
|---------------|-------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|---------------------|
| Type of LED | NF2W757GR-V3 |
|--------------------|---------------------|

| | |
|------------------------------|------------------------------|
| Average life time (h) | Up to 100,000hrs LM70 |
|------------------------------|------------------------------|


| | |
|-------------------------------|--------------|
| Colour temperature (K) | 4500K |
|-------------------------------|--------------|

| | |
|----------------------------------|--------------|
| Colour consistency (SDCM) | <5 |
|----------------------------------|--------------|

| | |
|------------|-----------|
| CRI | 75 |
|------------|-----------|

| | |
|-----------|-------------|
| IK | IK10 |
|-----------|-------------|

Scheme



Photometry

