INDUSTRIAL - SAFE





SAFE

Lavov outdoor floodlight from the family SAFE with a power of 50W and an optic of 26^ox60^o. With a totsl lumen output of 7250 Im and an efficiency of 145Im/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.


Item code	86.0F03.1461.02	
Product type		
Category	Industrial	
Family	SAFE	
Pictograms	$\bigoplus \begin{array}{ c c } \hline \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \hline \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \end{array} \\ \\ \hline \end{array} \\ \\ \\ \\$	
	CRI SDCM IP 70 5 65	

Dimensions

Product dimensions (mm)

353x287x65mm

Scheme



50W

Product	
Real power (W)	50
Real luminous flux (Lm)	7250
Luminous efficiency (Lm/W)	145
Beam angle (º)	26ºx60º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,95
Flicker Free	YES
Light source	LED
Average life time (h)	Up to 100,000hrs LM84
Colour temperature (K)	4000K
Colour consistency (SDCM)	<5
CRI	70
ІК	IK08

