



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of 25°. . With a total lumen output of 14500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Item code	86.OF03.3421.02
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Industrial
-----------------	-------------------

Family	SAFE
---------------	-------------


Pictograms	    
-------------------	---



Dimensions

Product dimensions (mm)	447x359x75mm
--------------------------------	---------------------

Scheme



80W/100W

Product

Real power (W)	100
-----------------------	------------

Real luminous flux (Lm)	14500
--------------------------------	--------------

Luminous efficiency (Lm/W)	145
-----------------------------------	------------

Beam angle (°)	25°
-----------------------	------------

IP	IP66
-----------	-------------

Operating temperature	-30°C to + 50°C
------------------------------	------------------------

Colour	black
---------------	--------------

Control gear included	yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Power Factor	>0,97
---------------------	-----------------

Flicker Free	YES
---------------------	------------

Light source	LED
---------------------	------------

Average life time (h)	Up to 100,000hrs LM72
------------------------------	------------------------------

Colour temperature (K)	4000K
-------------------------------	--------------

Colour consistency (SDCM)	<5
----------------------------------	--------------

CRI	70
------------	-----------

IK	IK08
-----------	-------------