



SAFE

IK

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of 25 $^{\circ}$. . With a totsl lumen output of 14500 \mbox{Im} and an efficiency of 145 $\mbox{Im}/\mbox{W}.$ Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Item code	86.OF03.3421.02
Product type	Outdoor
Category	Floodlights
Family	SAFE
Pictograms	☐ IK C € Driver INCL.
	CRI 5DCM IP 67

item code	00101 0313421102
Product type	Outdoor
Category	Floodlights
Family	SAFE
Pictograms	⇒ IK C € Driver INCL.
	CRI 5DCM IP 5 67

Product	
Real power (W)	100
Real luminous flux (Lm)	14500
Luminous efficiency (Lm/W)	145
Beam angle (º)	25º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,97
Flicker Free	YES
Light source	LED
Average life time (h)	Up to 100,000hrs LM72
Colour temperature (K)	4000K
Colour consistency (SDCM)	<5
CRI	70

IK08

Dimensions

Product dimensions (mm) 447x359x75mm

Scheme





