



## SAFE

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of  $60^{\underline{o}}.$  . With a totsl lumen output of 14500  $\mbox{Im}$  and an efficiency of 145  $\mbox{Im}/\mbox{W}.$  Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Item code	86.OF03.3431.02
Product type	Indoor
Category	Industrial
Family	SAFE
Pictograms	B50° IK CE Driver INCL.
	CRI SDCM IP 5 67

lustrial
FE
SDCM IP 67

Product	
Real power (W)	100
Real luminous flux (Lm)	14500
Luminous efficiency (Lm/W)	145
Beam angle (º)	60⁰
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,97
Flicker Free	YES
Average life time (h)	Up to 100,000hrs LM79
Colour temperature (K)	4000
Colour consistency (SDCM)	<5
CRI	70
IK	IK08

## **Dimensions**

**Product dimensions (mm)** 

447x359x75mm

## Scheme





