



**SAFE**

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of 60°. . With a total lumen output of 14500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.


<b>Item code</b>	<b>86.OF03.3433.02</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Floodlights</b>
<b>Family</b>	<b>SAFE</b>

<b>Pictograms</b>	

**Dimensions**

**Product dimensions (mm)** 447x359x75mm

**Scheme**



80W/100W

**Product**

<b>Real power (W)</b>	<b>100</b>
<b>Real luminous flux (Lm)</b>	<b>14500</b>
<b>Luminous efficiency (Lm/W)</b>	<b>145</b>
<b>Beam angle (°)</b>	<b>60°</b>
<b>IP</b>	<b>IP66</b>
<b>Operating temperature</b>	<b>-30°C to + 50°C</b>
<b>Colour</b>	<b>black</b>
<b>Control gear included</b>	<b>yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Power Factor</b>	<b>&gt;0,97</b>
<b>Flicker Free</b>	<b>YES</b>
<b>Light source</b>	<b>LED</b>
<b>Average life time (h)</b>	<b>Up to 100,000hrs LM79</b>
<b>Colour temperature (K)</b>	<b>4000K</b>
<b>Colour consistency (SDCM)</b>	<b>&lt;5</b>
<b>CRI</b>	<b>70</b>
<b>IK</b>	<b>IK08</b>