Dimensions

Scheme

Product dimensions (mm)





SAFE

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of $55^{o}\text{X}125^{o}\text{.}$. With a totsl lumen output of 14500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Item code	86.0F03.3451.02 Indoor Industrial SAFE		
Product type			
Category			
Family			
Pictograms	⇒ IK C€ Driver INCL.		
	CRI SDCM IP 67		

Product type Category	Indoor		
	Industrial		
Family	SAFE		
Pictograms	B50° IK C C Driver INCL.		
	CRI SDCM IP 67		

TW KINE TW KINE	300 M7		

447x359x75mm

Product	
Real power (W)	100
Real luminous flux (Lm)	14500
Luminous efficiency (Lm/W)	145
Beam angle (º)	55ºX125º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,97
Flicker Free	YES
Average life time (h)	Up to 100,000hrs LM72
Colour temperature (K)	4000
Colour consistency (SDCM)	<5
CRI	70
IK	IK08

