**INDUSTRIAL - SAFE** 





## SAFE

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of 26<sup>o</sup>x60<sup>o</sup>. With a totsl lumen output of 14500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.


| Item code    | 86.OF03.3461.02                             |  |
|--------------|---|--|
| Product type |   |  |
| Category     | Industrial                                  |  |
| Family       | SAFE  |  |
| Pictograms   | ⇒<br><sup> </sup> →  IK C € Driver<br>INCL. |  |
|              | CRI SDCM IP<br>70 5 67                      |  |

## Dimensions

**Product dimensions (mm)** 

447x359x75mm

## Scheme



80W/100W

| Product                    |                       |
|----------------------------|-----------------------|
| Real power (W)             | 100                   |
| Real luminous flux (Lm)    | 14500                 |
| Luminous efficiency (Lm/W) | 145                   |
| Beam angle (º)             | 26ºx60º               |
| IP                         | IP66                  |
| Operating temperature      | -30°C to + 50°C       |
| Colour                     | black                 |
| Control gear included      | yes                   |
| Control gear               | ON-OFF                |
| Power Factor               | >0,97                 |
| Flicker Free               | YES                   |
| Light source               | LED                   |
| Average life time (h)      | Up to 100,000hrs LM86 |
| Colour temperature (K)     | 4000K                 |
| Colour consistency (SDCM)  | <5                    |
| CRI                        | 70                    |
| К                          | IK08                  |

