FLOODLIGHTS - SAFE





SAFE

Lavov outdoor floodlight from the family SAFE with a power of 100W and an optic of 26^ox60^o. With a totsl lumen output of 14500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.


| Item code | 86.0F03.3461.02 Outdoor Floodlights | |
|--------------|---|--|
| Product type | | |
| Category | | |
| Family | SAFE | |
| Pictograms | B50° IK CE Driver INCL | |
| | CRI 5DCM IP 70 5 67 | |

Dimensions

Product dimensions (mm)

447x359x75mm

Scheme



80W/100W

| Product | | | |
|----------------------------|-----------------------|--|--|
| Real power (W) | 100 | | |
| Real luminous flux (Lm) | 14500 | | |
| Luminous efficiency (Lm/W) | 145 | | |
| Beam angle (º) | 26ºx60º | | |
| IP | IP66 | | |
| Operating temperature | -30°C to + 50°C | | |
| Colour | black | | |
| Control gear included | yes | | |
| Control gear | ON-OFF | | |
| Power Factor | >0,97 | | |
| Flicker Free | YES | | |
| Light source | LED | | |
| Average life time (h) | Up to 100,000hrs LM86 | | |
| Colour temperature (K) | 4000K | | |
| Colour consistency (SDCM) | <5 | | |
| CRI | 70 | | |
| IK | IK08 | | |

