



SAFE

IK

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 25 $^{\circ}$. . With a totsl lumen output of 21750 \mbox{Im} and an efficiency of 145 $\mbox{Im}/\mbox{W}.$ Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

Item code	86.OF03.4423.02
Product type	Indoor
Category	Industrial
Family	SAFE
Pictograms	⇒ IK C€ Driver INCL
	CRI SDCM 5

ream code	00101 0514425102
Product type	Indoor
Category	Industrial
Family	SAFE
Pictograms	⇒ NK 10 C€ Driver INCL.
	CRI SDCM 5

Product	
Real power (W)	150
Real luminous flux (Lm)	21750
Luminous efficiency (Lm/W)	145
Beam angle (º)	25º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	DALI
Power Factor	>0,98
Flicker Free	YES
Average life time (h)	Up to 100,000hrs LM73
Colour temperature (K)	4000
Colour consistency (SDCM)	<5
CRI	70
	-

IK08

Dimensions

Product dimensions (mm)

447x359x75mm

Scheme





