










SAFE

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 60°. . With a total lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

| | |
|--------------|---|
| Item code | 86.OF03.4431.02 |
| Product type | Outdoor |
| Category | Floodlights |
| Family | SAFE |
| Pictograms | <div><div></div><div> 850°</div><div> IK 10</div><div></div><div> Driver INCL.</div><div> CRI 70</div><div> SDCM 5</div></div> |

| Product | |
|----------------------------|-----------------------|
| Real power (W) | 150 |
| Real luminous flux (Lm) | 21750 |
| Luminous efficiency (Lm/W) | 145 |
| Beam angle (°) | 60° |
| IP | IP66 |
| Operating temperature | -30°C to + 50°C |
| Colour | black |
| Control gear included | yes |
| Control gear | ON-OFF |
| Power Factor | >0,98 |
| Flicker Free | YES |
| Light source | LED |
| Average life time (h) | Up to 100,000hrs LM80 |
| Colour temperature (K) | 4000K |
| Colour consistency (SDCM) | <5 |
| CRI | 70 |
| IK | IK08 |

Dimensions

| | |
|--------------------------------|---------------------|
| Product dimensions (mm) | 447x359x75mm |
|--------------------------------|---------------------|

Scheme

