



### SAFE

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 55°X125°. . With a total lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.OF03.4451.02</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                   |
|-----------------|-------------------|
| <b>Category</b> | <b>Industrial</b> |
|-----------------|-------------------|

|               |             |
|---------------|-------------|
| <b>Family</b> | <b>SAFE</b> |
|---------------|-------------|


|                   |   |
|-------------------|---|
| <b>Pictograms</b> |      |
|-------------------|---|



### Dimensions

|                                |                     |
|--------------------------------|---------------------|
| <b>Product dimensions (mm)</b> | <b>447x359x75mm</b> |
|--------------------------------|---------------------|

### Scheme



### Product

|                       |            |
|-----------------------|------------|
| <b>Real power (W)</b> | <b>150</b> |
|-----------------------|------------|

|                                |              |
|--------------------------------|--------------|
| <b>Real luminous flux (Lm)</b> | <b>21750</b> |
|--------------------------------|--------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>145</b> |
|-----------------------------------|------------|

|                       |                 |
|-----------------------|-----------------|
| <b>Beam angle (°)</b> | <b>55°X125°</b> |
|-----------------------|-----------------|

|           |             |
|-----------|-------------|
| <b>IP</b> | <b>IP66</b> |
|-----------|-------------|

|                              |                        |
|------------------------------|------------------------|
| <b>Operating temperature</b> | <b>-30°C to + 50°C</b> |
|------------------------------|------------------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>black</b> |
|---------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>yes</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                     |                 |
|---------------------|-----------------|
| <b>Power Factor</b> | <b>&gt;0,98</b> |
|---------------------|-----------------|

|                     |            |
|---------------------|------------|
| <b>Flicker Free</b> | <b>YES</b> |
|---------------------|------------|

|                     |            |
|---------------------|------------|
| <b>Light source</b> | <b>LED</b> |
|---------------------|------------|

|                              |                              |
|------------------------------|------------------------------|
| <b>Average life time (h)</b> | <b>Up to 100,000hrs LM73</b> |
|------------------------------|------------------------------|

|                               |              |
|-------------------------------|--------------|
| <b>Colour temperature (K)</b> | <b>4000K</b> |
|-------------------------------|--------------|

|                                  |              |
|----------------------------------|--------------|
| <b>Colour consistency (SDCM)</b> | <b>&lt;5</b> |
|----------------------------------|--------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>70</b> |
|------------|-----------|

|           |             |
|-----------|-------------|
| <b>IK</b> | <b>IK08</b> |
|-----------|-------------|