



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 55°X125°. . With a total lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Dimensions

Product dimensions (mm) **447x359x75mm**

Scheme



150W

| | |
|--------------|-----------------|
| Item code | 86.OF03.4451.02 |
| Product type | Indoor |
| Category | Industrial |
| Family | SAFE |
| Pictograms | |

| | |
|----------------------------|-----------------------|
| Product | |
| Real power (W) | 150 |
| Real luminous flux (Lm) | 21750 |
| Luminous efficiency (Lm/W) | 145 |
| Beam angle (°) | 55°X125° |
| IP | IP66 |
| Operating temperature | -30°C to + 50°C |
| Colour | black |
| Control gear included | yes |
| Control gear | ON-OFF |
| Power Factor | >0,98 |
| Flicker Free | YES |
| Light source | LED |
| Type of LED | NF2W757GR-V3 |
| Average life time (h) | Up to 100,000hrs LM73 |
| Colour temperature (K) | 4000K |
| Colour consistency (SDCM) | 5 |
| CRI | 70 |
| IK | IK08 |