



**SAFE**

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 55°X125°. . With a total lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

|                     |                        |
|---------------------|------------------------|
| <b>Item code</b>    | <b>86.OF03.4453.02</b> |
| <b>Product type</b> | <b>Outdoor</b>         |
| <b>Category</b>     | <b>Floodlights</b>     |
| <b>Family</b>       | <b>SAFE</b>            |

**Pictograms**

|                                   |                              |
|-----------------------------------|------------------------------|
| <b>Product</b>                    |                              |
| <b>Real power (W)</b>             | <b>150</b>                   |
| <b>Real luminous flux (Lm)</b>    | <b>21750</b>                 |
| <b>Luminous efficiency (Lm/W)</b> | <b>145</b>                   |
| <b>Beam angle (°)</b>             | <b>55°X125°</b>              |
| <b>IP</b>                         | <b>IP66</b>                  |
| <b>Operating temperature</b>      | <b>-30°C to + 50°C</b>       |
| <b>Colour</b>                     | <b>black</b>                 |
| <b>Control gear included</b>      | <b>yes</b>                   |
| <b>Control gear</b>               | <b>DALI</b>                  |
| <b>Power Factor</b>               | <b>&gt;0,98</b>              |
| <b>Flicker Free</b>               | <b>YES</b>                   |
| <b>Light source</b>               | <b>LED</b>                   |
| <b>Average life time (h)</b>      | <b>Up to 100,000hrs LM73</b> |
| <b>Colour temperature (K)</b>     | <b>4000K</b>                 |
| <b>Colour consistency (SDCM)</b>  | <b>&lt;5</b>                 |
| <b>CRI</b>                        | <b>70</b>                    |
| <b>IK</b>                         | <b>IK08</b>                  |

**Dimensions**

**Product dimensions (mm)** 447x359x75mm

**Scheme**

