



## SAFE


Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of  $55^{\varrho}X125^{\varrho}.$  . With a totsl lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

Item code	86.0F03.4453.02 Indoor Industrial	
Product type		
Category		
Family	SAFE	
Pictograms	⊞ S50° IK C€ Driver INCL.	
	CRI 5DCM 5	

Category	SAFE SAFE		
Family			
Pictograms	⇒ IK C€ Driver		
	CRI SDCM 5		

Dimensions	
Product dimensions (mm)	447x359x75mm

## Scheme



Product	
Real power (W)	150
Real luminous flux (Lm)	21750
Luminous efficiency (Lm/W)	145
Beam angle (º)	55ºX125º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	DALI
Power Factor	>0,98
Flicker Free	YES
Light source	LED
Average life time (h)	Up to 100,000hrs LM73
Colour temperature (K)	4000K
Colour consistency (SDCM)	<5
CRI	70
IK	IK08

