



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 150W and an optic of 55°X125°. . With a total lumen output of 21750 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

Dimensions

Product dimensions (mm) **447x359x75mm**

Scheme



150W

| | |
|--------------|-----------------|
| Item code | 86.OF03.4453.02 |
| Product type | Indoor |
| Category | Industrial |
| Family | SAFE |
| Pictograms | |

| | |
|----------------------------|-----------------------|
| Product | |
| Real power (W) | 150 |
| Real luminous flux (Lm) | 21750 |
| Luminous efficiency (Lm/W) | 145 |
| Beam angle (°) | 55°X125° |
| IP | IP66 |
| Operating temperature | -30°C to + 50°C |
| Colour | black |
| Control gear included | yes |
| Control gear | DALI |
| Power Factor | >0,98 |
| Flicker Free | YES |
| Light source | LED |
| Type of LED | NF2W757GR-V3 |
| Average life time (h) | Up to 100,000hrs LM73 |
| Colour temperature (K) | 4000K |
| Colour consistency (SDCM) | 5 |
| CRI | 70 |
| IK | IK08 |