



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 200W and an optic of 60°. . With a total lumen output of 29000 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

| | |
|-----------|-----------------|
| Item code | 86.OF03.5431.02 |
|-----------|-----------------|

| | |
|--------------|--------|
| Product type | Indoor |
|--------------|--------|

| | |
|----------|------------|
| Category | Industrial |
|----------|------------|

| | |
|--------|------|
| Family | SAFE |
|--------|------|


| | |
|------------|---|
| Pictograms |      |
|------------|---|



Dimensions

| | |
|-------------------------|--------------|
| Product dimensions (mm) | 447x359x75mm |
|-------------------------|--------------|

Scheme



200W

Product

| | |
|----------------|-----|
| Real power (W) | 200 |
|----------------|-----|

| | |
|-------------------------|-------|
| Real luminous flux (Lm) | 29000 |
|-------------------------|-------|

| | |
|----------------------------|-----|
| Luminous efficiency (Lm/W) | 145 |
|----------------------------|-----|

| | |
|----------------|-----|
| Beam angle (°) | 60° |
|----------------|-----|

| | |
|----|------|
| IP | IP66 |
|----|------|

| | |
|-----------------------|-----------------|
| Operating temperature | -30°C to + 50°C |
|-----------------------|-----------------|

| | |
|--------|-------|
| Colour | black |
|--------|-------|

| | |
|-----------------------|-----|
| Control gear included | yes |
|-----------------------|-----|

| | |
|--------------|--------|
| Control gear | ON-OFF |
|--------------|--------|

| | |
|--------------|-------|
| Power Factor | >0,99 |
|--------------|-------|

| | |
|--------------|-----|
| Flicker Free | YES |
|--------------|-----|

| | |
|--------------|-----|
| Light source | LED |
|--------------|-----|

| | |
|-----------------------|-----------------------|
| Average life time (h) | Up to 100,000hrs LM81 |
|-----------------------|-----------------------|

| | |
|------------------------|-------|
| Colour temperature (K) | 4000K |
|------------------------|-------|

| | |
|---------------------------|----|
| Colour consistency (SDCM) | <5 |
|---------------------------|----|

| | |
|-----|----|
| CRI | 70 |
|-----|----|

| | |
|----|------|
| IK | IK08 |
|----|------|