



### SAFE

Lavov outdoor floodlight from the family SAFE with a power of 240W and an optic of 55°X125°. . With a total lumen output of 34800 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

<b>Item code</b>	<b>86.OF03.6451.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Industrial</b>
-----------------	-------------------

<b>Family</b>	<b>SAFE</b>
---------------	-------------


<b>Pictograms</b>	    
	 



### Dimensions

<b>Product dimensions (mm)</b>	<b>495x419x75mm</b>
--------------------------------	---------------------

### Scheme



### Product

<b>Real power (W)</b>	<b>240</b>
-----------------------	------------

<b>Real luminous flux (Lm)</b>	<b>34800</b>
--------------------------------	--------------

<b>Luminous efficiency (Lm/W)</b>	<b>145</b>
-----------------------------------	------------

<b>Beam angle (°)</b>	<b>55°X125°</b>
-----------------------	-----------------

<b>IP</b>	<b>IP66</b>
-----------	-------------

<b>Operating temperature</b>	<b>-30°C to + 50°C</b>
------------------------------	------------------------

<b>Colour</b>	<b>black</b>
---------------	--------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>ON-OFF</b>
---------------------	---------------

<b>Power Factor</b>	<b>&gt;0,100</b>
---------------------	------------------

<b>Flicker Free</b>	<b>YES</b>
---------------------	------------

<b>Light source</b>	<b>LED</b>
---------------------	------------

<b>Average life time (h)</b>	<b>Up to 100,000hrs LM75</b>
------------------------------	------------------------------

<b>Colour temperature (K)</b>	<b>4000K</b>
-------------------------------	--------------

<b>Colour consistency (SDCM)</b>	<b>&lt;5</b>
----------------------------------	--------------

<b>CRI</b>	<b>70</b>
------------	-----------

<b>IK</b>	<b>IK08</b>
-----------	-------------