



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 240W and an optic of 26^ox60^o. With a totsl lumen output of 34800 Im and an efficiency of 145Im/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.


Item code	86.OF03.6461.02 Indoor Industrial	
Product type		
Category		
Family	SAFE	
Pictograms	$\bigoplus \begin{array}{ c c } \hline \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \hline \begin{array}{c} \end{array} \\ \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} $	
	CRI SDCM 70 5	

Dimensions

Product dimensions (mm)

495x419x75mm

Scheme



240W/300W

Product	
Real power (W)	240
Real luminous flux (Lm)	34800
Luminous efficiency (Lm/W)	145
Beam angle (º)	26ºx60º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,100
Flicker Free	YES
Light source	LED
Average life time (h)	Up to 100,000hrs LM89
Colour temperature (K)	4000K
Colour consistency (SDCM)	<5
CRI	70
IK	IK08

