



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 240W and an optic of $26^{\varrho}x60^{\varrho}.$. With a totsl lumen output of 34800 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

Item code	86.OF03.6461.02
Product type	Indoor
Category	Industrial
Family	SAFE
Pictograms	⇒ Sio* IK C € Driver INCL.
	CRI SDCM

Product	
Real power (W)	240
Real luminous flux (Lm)	34800
Luminous efficiency (Lm/W)	145
Beam angle (º)	26ºx60º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,100
Flicker Free	YES

Real power (W)	240
Real luminous flux (Lm)	34800
Luminous efficiency (Lm/W)	145
Beam angle (º)	26ºx60º
IP	IP66
Operating temperature	-30°C to + 50°C
Colour	black
Control gear included	yes
Control gear	ON-OFF
Power Factor	>0,100
Flicker Free	YES
Light source	LED
Average life time (h)	Up to 100,000hrs LM89
Colour temperature (K)	4000K
Colour consistency (SDCM)	<5
CRI	70
IK	IK08

Dimensions

Product dimensions (mm) 495x419x75mm

Scheme



