



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 300W and an optic of 25°. . With a total lumen output of 43500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

| | |
|--------------|-----------------|
| Item code | 86.OF03.7423.02 |
| Product type | Indoor |
| Category | Industrial |
| Family | SAFE |


Pictograms



Dimensions

Product dimensions (mm) 495x419x75mm

Scheme



Product

| | |
|----------------------------|-----------------------|
| Real power (W) | 300 |
| Real luminous flux (Lm) | 43500 |
| Luminous efficiency (Lm/W) | 145 |
| Beam angle (°) | 25° |
| IP | IP66 |
| Operating temperature | -30°C to + 50°C |
| Colour | black |
| Control gear included | yes |
| Control gear | DALI |
| Power Factor | >0,101 |
| Flicker Free | YES |
| Light source | LED |
| Average life time (h) | Up to 100,000hrs LM76 |
| Colour temperature (K) | 4000K |
| Colour consistency (SDCM) | <5 |
| CRI | 70 |
| IK | IK08 |