



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 300W and an optic of 60°. . With a total lumen output of 43500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. DALI driver.

Item code	86.OF03.7433.02
-----------	-----------------

Product type	Indoor
--------------	--------

Category	Industrial
----------	------------

Family	SAFE
--------	------


Pictograms	    
------------	---



Dimensions

Product dimensions (mm)	495x419x75mm
-------------------------	--------------

Scheme



Product

Real power (W)	300
----------------	-----

Real luminous flux (Lm)	43500
-------------------------	-------

Luminous efficiency (Lm/W)	145
----------------------------	-----

Beam angle (°)	60°
----------------	-----

IP	IP66
----	------

Operating temperature	-30°C to + 50°C
-----------------------	-----------------

Colour	black
--------	-------

Control gear included	yes
-----------------------	-----

Control gear	DALI
--------------	------

Power Factor	>0,101
--------------	--------

Flicker Free	YES
--------------	-----

Light source	LED
--------------	-----

Average life time (h)	Up to 100,000hrs LM83
-----------------------	-----------------------

Colour temperature (K)	4000K
------------------------	-------

Colour consistency (SDCM)	<5
---------------------------	----

CRI	70
-----	----

IK	IK08
----	------