



SAFE

Lavov outdoor floodlight from the family SAFE with a power of 300W and an optic of 26°x60°. . With a total lumen output of 43500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low copper content perfect for aggressive environments and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

| | |
|------------------|------------------------|
| Item code | 86.OF03.7461.02 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | Industrial |
|-----------------|-------------------|

| | |
|---------------|-------------|
| Family | SAFE |
|---------------|-------------|


| | |
|-------------------|---|
| Pictograms |      |
|-------------------|---|



Dimensions

| | |
|--------------------------------|---------------------|
| Product dimensions (mm) | 495x419x75mm |
|--------------------------------|---------------------|

Scheme



Product

| | |
|-----------------------|------------|
| Real power (W) | 300 |
|-----------------------|------------|

| | |
|--------------------------------|--------------|
| Real luminous flux (Lm) | 43500 |
|--------------------------------|--------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 145 |
|-----------------------------------|------------|

| | |
|-----------------------|----------------|
| Beam angle (°) | 26°x60° |
|-----------------------|----------------|

| | |
|-----------|-------------|
| IP | IP66 |
|-----------|-------------|

| | |
|------------------------------|------------------------|
| Operating temperature | -30°C to + 50°C |
|------------------------------|------------------------|

| | |
|---------------|--------------|
| Colour | black |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|---------------------|------------------|
| Power Factor | >0,101 |
|---------------------|------------------|

| | |
|---------------------|------------|
| Flicker Free | YES |
|---------------------|------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|------------------------------|------------------------------|
| Average life time (h) | Up to 100,000hrs LM90 |
|------------------------------|------------------------------|

| | |
|-------------------------------|--------------|
| Colour temperature (K) | 4000K |
|-------------------------------|--------------|

| | |
|----------------------------------|--------------|
| Colour consistency (SDCM) | <5 |
|----------------------------------|--------------|

| | |
|------------|-----------|
| CRI | 70 |
|------------|-----------|

| | |
|-----------|-------------|
| IK | IK08 |
|-----------|-------------|