



SAFE


Lavov outdoor floodlight from the family SAFE with a power of 300W and an optic of $26^{\varrho}x60^{\varrho}.$. With a totsl lumen output of 43500 lm and an efficiency of 145lm/W. Manufactured in die cast aluminium alloy with low cooper content perfect for agressive environements and finished in powder coating in black color. Degree of protection IP66 and IK08. ON-OFF driver.

| Item code | 86.0F03.7461.02 | | |
|--------------|--------------------------|--|--|
| Product type | Outdoor Floodlights SAFE | | |
| Category | | | |
| Family | | | |
| Pictograms | ⊞ N IK C € Driver INCL | | |
| | CRI 5DCM 5 | | |

| Item code | oduct type Outdoor tegory Floodlights | | |
|--------------|--|--|--|
| Product type | | | |
| Category | | | |
| Family | | | |
| Pictograms | ⇒ IK C € Driver INCL. | | |
| | CRI 5DCM 5 | | |

| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 495x419x75mm |

Scheme



| Product | |
|----------------------------|-----------------------|
| Real power (W) | 300 |
| Real luminous flux (Lm) | 43500 |
| Luminous efficiency (Lm/W) | 145 |
| Beam angle (º) | 26ºx60º |
| IP | IP66 |
| Operating temperature | -30°C to + 50°C |
| Colour | black |
| Control gear included | yes |
| Control gear | ON-OFF |
| Power Factor | >0,101 |
| Flicker Free | YES |
| Light source | LED |
| Average life time (h) | Up to 100,000hrs LM90 |
| Colour temperature (K) | 4000K |
| Colour consistency (SDCM) | <5 |
| CRI | 70 |
| IK | IK08 |

