




**ING-SMINI**

Recessed Inground Floor from the family ING-SMINI with a power of 2W and a beam angle of 10 degrees. With a real lumen output of 136 lm, and an efficiency of 68lm/W, made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in Stainless Steel. IP67 and IK07 degree of protection. ON-OFF driver.

<b>Item code</b>	<b>86.OI18.2311.00</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Recessed Inground Floor</b>
<b>Family</b>	<b>ING-SMINI</b>
<b>Pictograms</b>	

**Scheme**



<b>Product</b>	
<b>Real power (W)</b>	<b>2</b>
<b>Real luminous flux (Lm)</b>	<b>136</b>
<b>Luminous efficiency (Lm/W)</b>	<b>68</b>
<b>Beam angle (°)</b>	<b>10</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>67</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>Stainless steel finishing</b>
<b>Control gear included</b>	<b>No</b>
<b>Light source</b>	<b>LED</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>
<b>IK</b>	<b>07</b>