



ING-AD

Lavov recessed inground floor from the family ING-AD adjustable, with a power of 2.5W and a 40 degrees beam angle. Finished in Stainless steel colour. Dimensions $\varnothing 95 \times 116 \text{mm}$. With a total lumen output of 145lm and a luminous efficiency of 58lm/W. CCT 3000. Driver ON-OFF. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK10

Dimensions

Product dimensions (mm) $\varnothing 95 \times 116 \text{mm}$

Scheme



| | |
|--------------|-------------------------|
| Item code | 86.OI20.1341.07 |
| Product type | Outdoor |
| Category | Recessed Inground Floor |
| Family | ING |
| Subfamily | ING-AD |
| Pictograms | |

| | |
|-----------------------------|-----------------|
| Product | |
| Real power (W) | 2.5 |
| Real luminous flux (Lm) | 145 |
| Luminous efficiency (Lm/W) | 58 |
| Beam angle (º) | 40 |
| Life time (h) | 50000h L80B10 |
| IP | 67 |
| Electrical class insulation | Class I |
| Colour | Stainless steel |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | 1x2W CREE |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |
| IK | IK10 |